



## CLENZA EG Epoxy haze remover



A non-acid cleaner to remove epoxy grout haze from tile, concrete and stone surfaces and safe to be used on marbles and other calcium based stones.

### Features / Benefits

- Non acidic
- Fast Acting
- Easy to Use & Economical
- Ideal for Interior & Exterior areas

### Substrates

- All types of tiles
- Marble and calcium based stones
- Cement terrazzo surface
- Porcelain Tile
- Vitrified Tile
- Glass Tiles
- Glass Mosaic Tile

### Areas of application

- For interior & exterior applications of Tiles and calcium based stone surfaces

### Certifications

Member of  
**Indian Green Building Council**



## MIXING AND APPLICATION:

Note: Shake the container well for one minute before opening the container for use.

- Use masking tape to cover the grout joints to avoid Clenza EG spill over the epoxy tile grout.
- Apply Clenza EG over the epoxy haze using the brush and scrub the affected area with nylon brush.
- Wait 20 – 30 minutes for the epoxy film to be loosened.
- Remove epoxy film using a clean cloth or brush.
- Multiple applications may be necessary.
- Cleanse the area with water and allow it to dry.

## TECHNICAL DATA

Appearance	Pale Yellow liquid
Specific gravity	1.04 – 1.07
PH	8-10

### Cautions :

Always protect neighboring surfaces including wood, carpet, metal, landscaping and other surfaces.

Avoid contact with metals.

Do not mix with ammoniated cleaners as harmful fumes may result

Please wear hand gloves, nose cover and wear eye protection before and while using the product.

KEEP OUT OF REACH OF CHILDREN.

### PACKAGING:

1 litre & 5 Litre cans

### COVERAGE:

15 – 100 Sft depending on the porosity of surface and intensity of haze on the surface.

### STORAGE:

After usage, close the container well sealed to avoid contamination and solvent loss. Store in original container only. Store and use between temperature 4° C and 40° C

### WARRANTY:

MYK LATICRETE India Pvt Ltd warrants that MYK LATICRETE® CLENZA EG is free from manufacturing defects and will not break down, deteriorate or disintegrate under normal usage for a period of One (1) year from date of purchase subject to the terms and conditions stated in MYK LATICRETE Product Warranty

### MAINTENANCE:

**NOTE:** All impregnating sealers and cleaners are maintenance products and hence surfaces applied with sealers need careful maintenance.

Maintenance of the sealed surfaces should not be done with general cleaner chemicals. Plain soft water is recommended to clean the surface. For periodic cleaning we recommend to use our MYK LATICRETE CLENZA AQ, neutral, water based cleaner. Acidic cleaners are STRICTLY NOT recommended. Please refer the Maintenance manual for more details.

### TECHNICAL SUPPORT:

Information is available by contacting

MYK Laticrete Technical service

Telephone: +91-40-30413100

Fax: +91-40-23378784

Email: [technicalservices@myklaticrete.com](mailto:technicalservices@myklaticrete.com)

### MYK LATICRETE INDIA PVT LTD

8-2-703/A, Fourth Floor, Leela Gopal Towers,  
Road No.12, Banjara hills, Hyderabad – 500 034.

Telephone: +91-40-30413100

Fax: +91-40-23378784

Email: [contact@myklaticrete.com](mailto:contact@myklaticrete.com)

### AVAILABILITY:

MYK LATICRETE materials -

For distributor information

Telephone: +91-40-30413100

Fax: +91-40-23378784

Email: [contact@myklaticrete.com](mailto:contact@myklaticrete.com)